



H05VV-F PVC Flexible Cable

Application:

For use in household appliances such as washing machines, spin dryers and refrigerators. Generally unsuitable for outdoor use or industrial applications.

Specification

No. of Core	Conductor		Insulation	Jacket	
	Section (mm ²)	Cond.	Nom. Thick(mm)	Nom. Thick(mm)	Nom. O.D.(mm)
2	0.75	24/0.21mm	0.60	0.80	6.20
2	1.00	32/0.21mm	0.60	0.80	6.40
2	1.50	30/0.26mm	0.70	0.80	7.40
2	2.50	50/0.26mm	0.80	1.10	9.20
3	0.75	24/0.21mm	0.60	0.80	6.60
3	1.00	32/0.21mm	0.60	0.80	6.80
3	1.50	30/0.26mm	0.70	0.80	8.10
3	2.50	50/0.26mm	0.80	1.10	10.00

Details

Conductor	Flexible plain copper conductor
Insulation	PVC (polyvinyl chloride)
Insulation Color	2 Cores: Blue, Brown 3 Cores: Green/Yellow, Blue, Brown 4 Cores: Green/Yellow, Brown, Black, Grey 5 Cores: Green/Yellow, Brown, Black, Grey, Blue
Jacket	PVC (polyvinyl chloride)
Jacket Color	Black or White
Voltage Rating	300/330V
Temperature Rating	0°C to +60°C
Minimum Bending Radius	6×overall diameter