



SPT Flexible Cable

SPT-1 LAMP CORD: 105° C 300V (UL/CSA)

SPT-2 LAMP CORD: 105° C 300V (UL/CSA)

SPT-3 LAMP CORD: 60° C 300V (UL/CSA)

Application:

SPT-1 Lamp cord, SPT-2 Lamp Cord, and SPT-3 Lamp Cord are indented for use in household appliances, including clocks, lamps, radios and fans.

Specification

Type	No. of Core	Conductor		Insulation		Jacket	
		AWG	Section (mm ²)	Nom. Thick(mm)	Nom. O.D.(mm)	Nom. Thick(mm)	Nom. O.D.(mm)
SPT-1	2	18	0.82			0.76	2.7×5.35
	3			0.38	2.15		3.0×8.7
SPT-2	2	18	0.82			1.14	3.5×6.9
		16	1.31				3.9×7.4
	3	18	0.82	0.38	2.15		3.7×8.7
		16	1.31	0.38	2.40		3.9×9.2
SPT-3	2	18	0.82			1.52	4.2×8.4
		16	1.31			1.52	4.5×9.0
		14	2.08			2.03	5.8×12.0
		12	3.31			2.41	7.0×14.0
	3	18	0.82	0.38	2.15	1.52	4.3×11.4
		16	1.31	0.38	2.40	1.52	4.5×12.2
		14	2.08	0.38	2.80	2.03	5.8×14.8
		12	3.31	0.38	2.41	2.41	7.0×16.8