



Loud Speaker Cable 2/16AWG -3

Application:

- 1, General purpose direct burial power limited circuit, fire alarm, tray and communications cable used in audio applications.
- 2, Soundsational premium round speaker cable

Specification

Conductor Stranded	65/34 AWG Bare Copper
No. of Conductor	2
Insulation Material	Foam Polypropylene
Nom. Insulation Thickness	0.009" (0.22mm)
O.D. of Insulation	0.076" (1.93mm)
Nom. Jacket Thickness	0.020" (0.50mm) PVC
O.D. of overall cable	0.192" (4.87 mm) PVC

Electrical Performance:

Nom. D.C. R. Resistance @ 20°:	4.06 ohms per 1000ø
Temperature Rating	-20° C to 75° C
Operating Voltage	300 V RMS Max
Capacitance Between Conductors@1KHz	25 pF/ft Nom.
Capacitance Between Conductors to Shield @1KHz	

Color Code:

Name	Insulation 1	Insulation 2	Jacket
Color	Black	Red	Varies

Welcome your OEM orders!

www.kt-elec.com



*Your complimentary
use period has ended.
Thank you for using
PDF Complete.*

[Click Here to upgrade to
Unlimited Pages and Expanded Features](#)

KINGTONE ELECTRONICS