


Unshielded Riser Security Cable 22AWG



Application:

- 1, Power-limited control circuits
- 2, Intercom, security, audio, and background music wiring
- 3, Suggested voltage rating: 300V

Security Cable Insulation and Jacket

- 1, Riser grade PVC, RoHS standard
- 2, Temperature Range: -20°C to +75°C

Specifications:

No. of Cond.	AWG SIZE	COND. STRAND	NOM.THICKNESS(MM)		Nominal O.D.	NEC TYPE
			INSUL.	Jacket		
2	22	Solid	0.20	0.38	3.00	CL3R/CMR
4	22	Solid	0.20	0.38	3.20	CL3R/CMR
2	22	7/30	0.20	0.38	3.10	CL3R/CMR
3	22	7/30	0.20	0.38	3.28	CL3R/CMR
4	22	7/30	0.20	0.38	3.96	CL3R/CMR
6	22	7/30	0.20	0.38	4.17	CL3R/CMR
8	22	7/30	0.20	0.38	4.57	CL3R/CMR
10	22	7/30	0.20	0.38	5.38	CL3R/CMR
12	22	7/30	0.20	0.38	5.56	CL3R/CMR

Color Code Chart:

No. of Conductors	1	2	3	4	5	6
Color	Black	Red	White	Green	Brown	Blue
	7	8	9	10	11	12
	Orange	Yellow	Violet	Gray	Pink	Tan

Welcome your OEM orders!
www.kt-elec.com