


## Unshielded Riser Security Cable 12AWG



### Application:

- 1, Power-limited control circuits
- 2, Intercom, security, audio, and background music wiring
- 3, Suggested voltage rating: 300V

### Security Cable Insulation and Jacket

- 1, Riser grade PVC, RoHS standard
- 2, Temperature Range: -20°C to +75°C

### Specifications:

| No. of Cond. | AWG SIZE | COND. STRAND | NOM.THICKNESS(MM) |        | Nominal O.D. | NEC TYPE |
|--------------|----------|--------------|-------------------|--------|--------------|----------|
|              |          |              | INSUL.            | Jacket |              |          |
| 2            | 12       | 19/0.0185    | 0.33              | 0.38   | 6.60         | CL3R/CMR |
| 4            | 12       | 19/0.0185    | 0.33              | 0.38   | 7.92         | CL3R/CMR |

### Color Code Chart:

| No. of Conductors | 1      | 2      | 3      | 4     | 5     | 6    |
|-------------------|--------|--------|--------|-------|-------|------|
| Color             | Black  | Red    | White  | Green | Brown | Blue |
|                   | 7      | 8      | 9      | 10    | 11    | 12   |
|                   | Orange | Yellow | Violet | Gray  | Pink  | Tan  |

Welcome your OEM orders!  
www.kt-elec.com