

## Loud Speaker Cable 2/14AWG -3



### Application:

- 1, General purpose direct burial power limited circuit, fire alarm, tray and communications cable used in audio applications.
- 2, Soundsational premium round speaker cable

### Specification

|                           |                          |
|---------------------------|--------------------------|
| Conductor Stranded        | 105/34 AWG Bare Copper   |
| No. of Conductor          | 2                        |
| Insulation Material       | Foam Polypropylene (FPE) |
| Nom. Insulation Thickness | 0.009" (0.22mm)          |
| O.D. of Insulation        | 0.091" (2.31mm)          |
| Nom. Jacket Thickness     | 0.020" (0.50mm) PVC      |
| O.D. of overall cable     | 0.222" (5.63 mm) PVC     |

### Electrical Performance:

|  |                     |
|--|---------------------|
| Nom. D.C. R. Resistance @ 20°:                 | 2.56 ohms per 1000ø |
| Temperature Rating                             | -20° C to 75° C     |
| Operating Voltage                              | 300 V RMS Max       |
| Capacitance Between Conductors@1KHz            | 25 pF/ft Nom.       |
| Capacitance Between Conductors to Shield @1KHz |                     |

### Color Code:

| Name  | Insulation 1 | Insulation 2 | Jacket |
|-------|--------------|--------------|--------|
| Color | Black        | Red          | Varies |

Welcome your OEM orders!

[www.kt-elec.com](http://www.kt-elec.com)