



Shielded Riser Security Cable 18AWG

Application:

- 1, Power-limited control circuits
- 2, Intercom, security, audio, and background music wiring
- 3, Suggested voltage rating: 300V

Security Cable Insulation and Jacket

- 1, Riser grade PVC, RoHS standard
- 2, Temperature Range: -20°C to +75°C

Specifications:

No. of Cond.	AWG SIZE	COND. STRAND	NOM.THICKNESS(MM)		Nominal O.D.	NEC TYPE
			INSUL.	Jacket		
2	18	Solid	0.22	0.38	3.73	CL3R/CMR
2	18	7/26	0.22	0.38	4.16	CL3R/CMR
3	18	7/26	0.22	0.38	4.36	CL3R/CMR
4	18	7/26	0.22	0.38	4.74	CL3R/CMR
6	18	7/26	0.22	0.38	5.84	CL3R/CMR
7	18	7/26	0.25	0.38	5.84	CL3R/CMR
8	18	7/26	0.22	0.38	6.35	CL3R/CMR
9	18	7/26	0.25	0.38	6.90	CL3R/CMR
10	18	7/26	0.22	0.38	7.28	CL3R/CMR
12	18	7/26	0.22	0.38	7.51	CL3R/CMR

Color Code Chart:

No. of Conductors	1	2	3	4	5	6
Color	Black	Red	White	Green	Brown	Blue
	7	8	9	10	11	12
	Orange	Yellow	Violet	Gray	Pink	Tan

Welcome your OEM orders!

www.kt-elec.com